



Talisman DC4 Hubset

Thank you for your purchase! We hope you're pleased with your new hubs and we're committed to offering the finest products at a great value to our customers. If there's anything we can do to assist, please let us know. The easiest & fastest way to reach us is by email – TalismanCycles@Gmail.com

Hub Measurements

Front

100 Total width, mm
22 WL, width from center to left flange
33 WR, width from center to right flange
56 dL, left flange diameter
56 dR, right flange diameter
2.5 S, spoke hole diameter
32 # of spoke holes

Rear

135 Total width, mm
36.5 WL, width from center to left flange
19.5 WR, width from center to right flange
56 dL, left flange diameter
56 dR, right flange diameter
2.5 S, spoke hole diameter
32 # of spoke holes

Compatibility

The DC4 hubset is optimized for Shimano/SRAM 8-9-10 speed HG-splined cassettes or SRAM 11 speed XD cassettes depending on the supplied freehub.

Maintenance

The DC4 hubset requires very little other than basic care. The one thing to keep an eye on is freehub lubrication as this will dramatically extend the life of the rear hub.

We recommend cleaning & lubricating the freehub pawls every few thousand miles or at least once per year.

If your freehub begins to sound significantly LOUDER – like a clacking instead of clicking – it is likely dry & should be oiled. Heavier oils work best, Phil Wood Tenacious Oil for example.



Don't use grease in place of oil, it can cause the pawls to stick & fail to engage.

This is a simple process that can be performed by any competent bike tech. No tools are required as the rear hub end caps are press-fit together. In fact the cassette can be left in place so long as no dirt falls from it into the freehub mechs. A plastic shopping bag works pretty well wrapped around the entire cassette body.

Drop us a pic of your new wheels once finished, we'd love to see what you create!